



Single-phase electricity meters DLMS

Single-phase electricity meter

AIST A100 ETHERNET

"AIST A 100" single-phase electric energy meter is designed for measuring and metering of active energy in single-phase alternating current circuits and transmission of telemetric information about the consumed electricity when used in automated data collection systems. Single-phase electronic electricity meter "AIST A100" performs the following functions:

- Voltage measurement;
- Current measurement;
- Calculation of active power;
- Registration of consumed energy;
- Countdown of time and calendar date;
- Information exchange with the concentrator by means of data transfer units (DTCs);
- Data storage in non-volatile memory.

Consumer and service data are displayed on the liquid crystal display (LCD) located on the front panel of the meter. The meter can be operated autonomously or in an automated system of data collection on the consumed electricity. It is possible to configure the meter parameters using a computer or a manual polling and programming device (MPD).

The meter allows to control electricity consumption taking into account the developed tariff structure. It is possible to receive information about the emergency state of the own network. Ethernet module allows to simplify remote reading of readings and additional information from the meters. Ethernet modules work in any Ethernet network and are fully compatible with the global Internet.

Technical specifications

Name of characteristic	Value
Accuracy class of active energy	1
Base, I _b (maximum) current, A	5 (60)
Rated voltage value (U _{nom}), V	230
Starting current (sensitivity threshold):	0.004·I _b
Set operating voltage range, V	0.9 to 1.1·U _{nom}
Extended voltage range, V	0.8 to 1.15·U _{nom}
Power consumption, V·A, not more: <ul style="list-style-type: none"> On the voltage circuit Current circuit 	5 0,2
Nominal value of mains frequency, Hz	50
Maximum number of tariffs	4
Minimum tariff duration, min	15
RS-485 interface communication speed, bps	1200~9600
Accuracy of the built-in clock when the counter is on and at normal temperature, better, c/day.	±0,5
Liquid crystal display (LCD): <ul style="list-style-type: none"> - Number of indicated digits - Unit value of the lowest digit when displaying energy, kW·h 	8 0,01
Meter constant, imp/(kWh)	1200
Average MTBF, h	at least 160 000
Service life of the meter clock power supply, years	at least 10
Additional I/O units	RF modem, PLC modem, GSM modem
Temperature range, °C	from - 40 to +55
At temperatures from - 20 to - 40 °C partial loss of LCD functionality is allowed	
Overall dimensions (height×width×depth), mm:	190×113×75
Counter weight, kg	no more than 2.8
<i>Specific characteristics for a particular type of module:</i>	
Ethernet module	Up to 100 Mbps data transfer rate via 10100 Base T interface
<i>Common characteristics for all modules:</i>	
Power supply voltage	12 volts
Consumption current	max. 125mA
Power supply of the device	is supplied by the AIST electricity meter
Average MTBF	at least 150000 h
Service life	20 years
Overall dimensions	70 x 50 x 28 mm